



NEW DELHI

816, Laxmi Deep,
Laxmi Nagar, New Delhi
Mob: +91- 9762725249
Email: enquiry.arko@gmail.com

GHAZIABAD

M/S. ARK099 PLASTIC AND STEELS
Cm-31c, 1st Floor
Gagan Enclave
Gt Road , Ghaziabad
U.P. 201001
0120-2866969

KOLKATA

M/S. BUILDCON
137/ E, Picnic Garden Road,
Ground Floor, Kolkata , West Bengal- 700039
Mob - 8240284302
Email - wbsales.arko@gmail.com

GUWAHATI

M/S. L. P. ASSOCIATES
Nar-narayan Road
West Durgasarobar
Kamakhya Gate, Guwahati
781009, Assam
Mob - 9864062866
Email - sushil.lpa@gmail.com

GWALIOR

Bindal Plywood, Behind
Old Police Chowky, Daulatganj
Lashkar, Gwalior
M.P.- 474001
Mob -9762725249

ARKO BUILDING PRODUCTS PVT. LTD

www.arkobuildingproducts.com

AN ISO
9001:2015
CERTIFIED

INTRODUCING PROTECH PUF PANEL COLD ROOM PRE-FABRICATED ROOMS

ROOFING

PRE - FABRICATED OFFICE

COLD ROOMS

WE DON'T
JUST SUPPLY
WE BUILD

MEDICAL CLEAN ROOM

PURLIN & SECTIONS

ABOUT US

Arko Product Portfolio are Roofing Sheets, Puf Sandwich Panels, Galvalume & Galvanized Color Coated SMP/RMP Sheets, Decking Sheets, Polycarbonate Sheets, Skylight Polycarbonate Multiwall, Self Drilling Screws, Purlins, PEB building.

24/7 Emergency Available



Satisfaction Guarantee



Expert and Professional



Free Inspection



OUR PRODUCTS & SERVICES

- ARKO commenced its operations in 2014, and pioneered the high-end Puf Panel products market in India.
- Arko has been the first mover in India, who gives service after sales. We are not just supplying we deliver the projects.
- We are also involved in installation service for all over INDIA and foreign.
- ARKO Team are having years of expreience in supplying and installing of pre-fabricated panels like - Roof Panel, Wall Panel, Ceiling Panels, Cold Room, Clean Room, Pre Fab Shelters, Mushroom Rooms, Office Rooms



Pre Fabricated Rooms With PEB Structure



PRE FABRICATED ROOMS



Pre Fabricated Rooms With False Ceiling



ROOFING & CLADDING SYSTEMS



Wall Panel Partition



Clean Rooms

PROTECH ROOF PANEL






ROOF PANEL

ROOFING SYSTEMS

PROTECH ROOF metal roof panel is the most versatile roofing product in the market and offers you both elegance and thermal conductivity for any building need.

Long lengths and weatherproof side lap allow PROTECH to be used safely on roof pitches as low as 3 degree in single sheet lengths, 5 degree with end laps, and for vertical cladding.



PROTECH 5 PROFILE


SUPPLY WIDTH - 1080 mm
COVERED WIDTH - 1010 mm
C TO C - 250 mm
CREST HEIGHT - 30 mm

PROTECH 6 PROFILE

SUPPLY WIDTH - 1060 mm
COVERED WIDTH - 980 mm
C TO C - 200 mm
CREST HEIGHT - 28 mm

PU PANEL PROPERTIES

PUF THICKNESS: 30 mm TO 120 mm
PUF DENSITY: 40 KG M³
TEMPERATURE RANGE: -40° TO 80° C
COMPRESSIVE STRENGTH: 110 - 210 kPA
ADHESION STRENGTH: 110 - 210 kPA
TENSILE STRENGTH: 370 kPA
WATER ABSORPTION: 0.2% Max. AT R.H 98%
THERMAL CONDUCTIVITY: ≤0.02 W/m.k at 23° C
FIRE PROPERTY: SELF EXTINGUISHING*
CLOSED CELL CONTENT: >95%
TOP SHEET: 0.40 TO 0.60 mm (CUSTOMIZE'S)
BOTTOM SHEET: 0.30 TO 0.60 mm (CUSTOMIZE'S)
COATING: PPGI OR PPGL OR BARE GALVALUME OR STAINLESS STEEL






WALL PANEL

WALL & PARTITION SYSTEMS

PROTECH Wall Panel are typically factory made units which consists of an insulating layer of rigid PUF between two layer of metal sheet, It is highly suitable for faster construction, energy saving and money saving. The advanced technology of manufacturing ensures superior quality and performance of the PUF product considering the heat insulation, sound insulation, water resistance, chemical and alkali resistance, corrosion proof, fire retardant, eco friendly, easy to install and move, light weight as well as cost effective in installation and it can save construction cost up to 60%.

Cam Lock WALL & CEILING PANEL



NOTE:

Length Can Be Customizable Upto 9 Mtr (Subject To Transportation)

1190 mm Width for 30 , 40, 50 mm

1180 mm Width for 60, 80 mm

1170 mm Width for 90, 120 mm

| PU PANEL PROPERTIES |

PUF THICKNESS: 30 mm TO 120 mm

PUF DENSITY: 40 KG M³

TEMPERATURE RANGE: -40° TO 80° C

COMPRESSIVE STRENGTH: 110 - 210 kPA

ADHESION STRENGTH: 110 - 210 kPA

TENSILE STRENGTH: 370 kPA

WATER ABSORPTION: 0.2% Max. AT R.H 98%

THERMAL CONDUCTIVITY: ≤0.02 W/m.k at 23° C

FIRE PROPERTY: SELF EXTINGUISHING*

CLOSED CELL CONTENT: >95%

TOP SHEET: 0.40 TO 0.60 mm (CUSTOMIZE'S)

BOTTOM SHEET: 0.30 TO 0.60 mm (CUSTOMIZE'S)

COATING: PPGI OR PPGL OR BARE GALVALUME
OR STAINLESS STEEL

PROTECH

WALL &
CEILING

PANEL



DOORS & WINDOWS

HINGE DOOR, HATCH DOOR, INDUSTRIAL DOOR
CLEAN ROOM DOOR



HINGED DOOR /
HATCH DOOR /
CLEAR ROOM DOOR

#Various types such as single leaf or double lead, overlapping or flush

#Standard size of doors 900 mm x 2100 mm

#Insulated with CFC free PU of density 40kg/m³

#Aluminum or SS railing for high durability

#For Chiller application temperature upto +20 Deg C - 60mm

#For Freezer/Blast Freezer with tem below -40 Deg C application
- 150mm/200mm

Windows

Strong and light weight


Quick to install

Option of colour range and design


Various thickness available




FLASHINGS




GABLE FLASHING




APRON FLASHING



RIDGE CAP



TOP CORNER



L CORNER



Arko team are expert with 25 years experience to provide you solution for your building, Our experts generate bill of quantity as per actual needs which saves your money and wastage. Arko are handling projects with 200+ workers in pan India. We provide free inspection service at your door, We use proper safety equipments like Safety Belt, Safety Shoes, Helmet, Gloves, Eye Protector, High Visibility Jacket, Ear Protector. Arko uses only high quality SCREWS, SILICON SEALANT, CAPS, BUTYL TAPE AND ANCHOR FASTENERS.

PROTECH FLASHING | INSTALLATION



CLEAN ROOM
MEDICAL ROOM



PREFABRICATED
ROOMS
SITE OFFICE
GUARD CABIN

